

SPAX[®]



VERDA[®]
OUTDOOR



Everything for your deck

SPAX[®]-D makes screwing easy.





Step 1:

Drill the boards and sub-structure with a SPAX® Ø 3.5 mm wood drill. Use the complete length of the drill. Use the highest possible speed (around 3,000 rpm).



Step 2:


Drive the SPAX®-D straight in with a SPAX® T-STAR plus T25 bit. Drive it in without stopping until the head is flush.



Result:

Perfect look thanks to the cylindrical screw head. No splitting of the wood even close to the edge.

The fixing thread ensures a tight joint between the wooden parts (vice effect).



SPAX®-D A2



The unique decking screw for wooden terraces.

SPAX®-D: The outdoor decking screw with three way action.

- Patented ground serrations on the lower thread remove the need for pre-drilling*
- Non threaded shank allows two materials to be pulled together tightly
- Upper thread locks the deck-board securely down tight



Dimensions [mm]				Packaging units	Product code
Thread Ø d1	Total length Ls	Partial thread length LgT	Bit size T	SPAX® BOX [pieces]	
5,0	40	22,5	25	200	0537000500403
	50	22,5	25	200	0537000500503
	60	27,5	25	100	0537000500603
	70	32,5	25	100	0537000500703
	80	37,5	25	100	0537000500803



Cylindric head:
Sits flush in the wood.

Fixing thread:
Two wooden planks are drawn close together – the upper plank will not come loose.

Ground serrations:
Ease in turning the screw into the wood right up to the point.

CUT point:
Prevents wood splitting by gripping immediately.

* We recommend pre-drilling in hardwoods






Step 1:

Drill the boards and sub-structure with a SPAX® Ø 3.5 mm wood drill. Use the complete length of the drill. Use the highest possible speed (around 3,000 rpm).



Step 2:


Drive the SPAX®-D straight in with a SPAX® T-STAR plus T25 bit. Drive it in without stopping until the head is flush.



Result:

Perfect look thanks to the cylindrical screw head. No splitting of the wood even close to the edge.

The fixing thread ensures a tight join between the wooden parts (vice effect).




SPAX®-D A4

*The unique decking screw for wooden terraces.
Particularly well suited for coastal areas.*

- Patented ground serrations on the lower thread remove the need for pre-drilling*
- Non threaded shank allows two materials to be pulled together tightly
- Upper thread locks the deck-board securely down tight
- Permanent protection against corrosion



Dimensions [mm]				Packaging units	Product code
Thread Ø d1	Total length Ls	Partial thread length LgT	Bit size T	SPAX® BOX [pieces]	
5,5	40	22,5	25	200	0538000550403
	50	22,5	25	200	0538000550503
	60	27,5	25	100	0538000550603
	70	32,5	25	100	0538000550703
	80	37,5	25	100	0538000550803



Cylindric head:
Sits flush in the wood.

Fixing thread:
Two wooden planks are drawn close together – the upper plank will not come loose.

Ground serrations:
Ease in turning the screw into the wood right up to the point.

CUT point:
Prevents wood splitting by gripping immediately.



* We recommend pre-drilling in hardwoods

